

eRed Folder : [Previous Doc](#) [Next Doc](#) [Go to Doc#](#)
[First Hit](#)☐

L33: Entry 5 of 5

File: JPAB

Feb 25, 2000

DOCUMENT-IDENTIFIER: JP 2000055656 A
TITLE: TILT SENSORAbstract Text (2):

SOLUTION: In a tilt sensor, metal balls 1 are interposed at a gap between light-receiving/emitting elements of a photo-interrupter for detecting an existence or non-existence of an object to be detected by receiving a light from an emitting element by a light-receiving element through a gap and a direction, an angle and so on are detected by a signal from a plurality of outputs by a position of the balls 1. In this case, a ball-accommodating portion of a mold body 4a accommodating the metal balls 1 is formed to an n-sided polygon (n = an even number of 4 or more, for example, 4) and the number of the metal balls 1 is n/2 (quadrangle = 2). By forming the same number of light-receiving windows 7a, 7b as the number of the metal balls 1 on a light-receiving surface side of the mold body 4a, the metal balls 1 are moved by an inclination of the tilt sensor and shields the light-receiving windows 7a, 7b. Thereby, a detection of n directions (four or more directions) can be realized by one tilt sensor.

[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)